EDGE electric pallet trucks

PTE15N / PTE20N

Rated load: 1,500 kg / 2,000 kg

AT A GLANCE

Two electric pallet truck models for pallet handling. The table below reproduces the specifications listed on the manufacturer's product page.

Specification	PTE15N	PTE20N
Rated load	1,500 kg	2,000 kg
Tiller height, drive position (min. / max.)	700 / 1,160 mm	700 / 1,160 mm
Turning radius	1,330 mm	1,336 mm
Travel speed (laden / unladen)	4.6 / 4.8 km/h	4.8 / 5.2 km/h
Battery voltage / capacity	24 V / 20 Ah (24 V / 36 Ah)	48 V / 20 Ah

Battery notation is retained from the source; the parenthesised PTE15N capacity is not explained on the page.

ILLUSTRATED PRODUCT DETAILS

The following pages preserve the manufacturer's illustrations. The 1,500 kg capacity, 123 kg weight and ramp figures shown in those graphics relate to the illustrated 1,500 kg version; do not assume they apply to the PTE20N.

Source: NOBLELIFT product page | Accessed 28 October 2026

View the original product page

Product design



Applications and highlights










Controls and handling



The tiller of the truck is supported by the **air spring** and the tiller returns to its vertical position smoothly.

Speed reduction at different angles as well as function of active tiller in its up-right position.



Emergency-reverse &Horn Buttons

Dual butterfly-style thumb driving controls

Electric lifting and lowering

Turtle Speed Button

Smart **Pin Code** Access



Battery discharge indicator

Operating hour counter

On-board diagnostics via error codes



Capacity up to **1500 kg** and ability to overcome ramps up to **4/16%** (laden/ unladen) makes the truck suitable for work in loading docks and on delivery operations in different conditions

